


REVISIONS				
REV.	DATE	DESCRIPTION	ECO	BY
A	04-25-07	PRODUCTION RELEASE	11573	DN
B	02-06-08	ADD P/N: 140-0665	11796	RKL
C	01-06-10	REPLACE 120-0495 (6) FOR 120-0496 (6), REPLACE 120-3281 (2) FOR 120-3316 (2); ADD NOTE 9; UPDATE NOTE 5; WAS 200 LB-IN/16.5 LB-FT/ 22.5 N-M IS 150 LB-IN/12.5 LB-FT/16.9 N-M; ADD 721-1150 (1); ON SHT 2: ADD DETAIL VIEW F, G, & H.	12293	SCN

ITEM NO.	PART NUMBER	DESCRIPTION	Default/ QTY.	Notes
1	020-6623-05	GUARD,DISK PLATE,TBT	2	
2	020-6764	BRACKET, UPPER SHROUD MOUNT	1	
3	020-6781	WASHER, HAT, UB LINKAGE	4	
4	020-6796	BRACKET, ELEC. GUIDE EL6200	1	
5	020-6797	DUST COVER, LCB & UB PCBS	1	
6	020-6867-05	LINK,PEDAL ARM,TBT	2	
7	110-1510	BOLT, 5/16-18 X 1.75 L, HH	1	
8	110-1870	NUT, 5/16-18 KEPS	2	
9	110-2150	SCREW, 1/4-20X1/2,SHC,HE,AS,BO	10	REF
10	110-3026	SCREW, 10-24X.50\"/>		

- NOTES: UNLESS OTHERWISE SPECIFIED
- TORQUE TO 100 LB-FT.
 - TORQUE TO 65 LB-FT.
 - ACCURATE ORIENTATION OF P/N 120-3293 IS REQUIRED FOR ITS FUNCTIONALITY.
 - FOR WIRING DIAGRAM REFER TO 620-7487.
 - TORQUE TO 150 LB-IN / 12.5 LB-FT / 16.9 N-M.
 - TORQUE TO 130 LB-IN / 10.5 LB-FT / 14.5 N-M.
 - TORQUE TO 240 LB-IN / 20 LB-FT / 27 N-M.
 - APPLY MOLY LUBE/ANTI-SEIZE LUBE (MIL-A907E OR EQUIV.) TO CRANK SHAFT BEARING SURFACE (BOTH SIDES)
 - ADJUST U/B HARD STOP WHEN U/B IS IN NONE POSITION

DOCUMENT STATUS:

NOTICE OF PROPRIETARY INFORMATION
 THIS DOCUMENT SHALL NOT BE REPRODUCED NOR SHALL THE INFORMATION CONTAINED HEREIN BE USED BY OR DISCLOSED TO OTHER EXCEPT AS EXPRESSLY AUTHORIZED BY UNISEN INC. D.B.A. STAR TRAC.



MATERIAL SEE BOM	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. TOLERANCES ARE: DECIMALS .X = ±.13 .XX = ±.05 .XXX = ±.03 X.XXX = ±.010	UNISEN, INC. DBA 14410 Myford Road Irvine CA 92606
FINISH NONE	INITIAL DN DATE 4/05/07	STARTRAC PART NO 721-1151
VENDOR: P/N:	DRAWN CHECKED APPROVED	TITLE ASSY, UB LINKAGES AND LEGS,P-TBTx
	U.O.M. INCH	SCALE: 1:7 SHEET 1 OF 2 SHEET SIZE: C

