

MSDS Sheet for Calwax:

**Star Trac Part Numbers: 800-3146
 140-3180**

Material Safety Data Sheet Info

SECTION I - Material Identity
SECTION II - Manufacturer's Information
SECTION III - Physical/Chemical Characteristics
SECTION IV - Fire and Explosion Hazard Data
SECTION V - Reactivity Data
SECTION VI - Health Hazard Data
SECTION VII - Precautions for Safe Handling and Use
SECTION VIII - Control Measures
SECTION IX - Label Data
SECTION X - Transportation Data
SECTION XI - Site Specific/Reporting Information
SECTION XII - Ingredients/Identity Information

SECTION I - Material Identity

Item Name	
Part Number/Trade Name	CALWAX EXTRUSIONS
National Stock Number	9160P2S738
CAGE Code	CALWA
Part Number Indicator	A
MSDS Number	182437
HAZ Code	B

SECTION II - Manufacturer's Information

Manufacturer Name	CALWAX CORP
Street	155 N. ASPAN AVE
City	AZUSA
State	CA
Country	US
Zip Code	91702
Emergency Phone	818-969-4334

MSDS Preparer's Information

Date MSDS Prepared/Revised	00JUN94
Active Indicator	N

Alternate Vendors

Vendor #1 CAGE	CALWA
----------------	-------

SECTION III - Physical/Chemical Characteristics

Appearance/Odor	SOLID GREEN MATERIAL; NO ODOR
Boiling Point	>600 F
Specific Gravity	.930
Evaporation Rate	N/A
Solubility in Water	INSOLUBLE
Container Pressure Code	4
Temperature Code	8
Product State Code	S

SECTION IV - Fire and Explosion Hazard Data

Flash Point Method	UNK
Lower Explosion Limit	N/A
Upper Explosion Limit	N/A
Extinguishing Media	CO2, FOAM, DRY CHEMICAL, WATER FOG
Special Fire Fighting Procedures	NONE
Unusual Fire/Explosion Hazards	NONE

SECTION V - Reactivity Data

Stability	YES
Stability Conditions to Avoid	NONE
Materials to Avoid	NONE
Hazardous Decomposition Products	NONE
Hazardous Polymerization	NO
Polymerization Conditions to Avoid	WILL NOT OCCUR

SECTION VI - Health Hazard Data

Route of Entry: Skin	YES
Health Hazards - Acute and Chronic	BURN FROM MOLTEN WAX WILL CAUSE THERMAL BURN
Emergency/First Aid Procedures	SKIN: A BURN FROM HOT MOLTEN WAX SHOULD BE TREATED AS A THERMAL BURN, COOL WAX ASAP W/TAP WATER

SECTION VII - Precautions for Safe Handling and Use

Steps if Material Released/Spilled	IF SOLID SWEEP UP SPILLED MATERIAL. IF HOT, CONFINE SPILL AND LET WAX SOLIDIFY
Waste Disposal Method	BURN IN AN APPROVED HYDROCARBON INCINERATOR OR BURY IN A APPROVED LAND FILL
Handling and Storage Precautions	STORE AWAY FROM OPEN FLAME AND BOILERS
Other Precautions	SOME STATIC CHARGE MAY OCCUR WHEN TRANSFERRING GROUND OR PARTICULARIZED WAX. GROUNDING SHOULD BE PROVIDED FOR ALL EQUIP

SECTION VIII - Control Measures

Respiratory Protection	NONE REQUIRED FOR HANDLING SOLID WAX. USE DUST RESPIRATOR IF GROUND OR SMALL PARTICULARIZED WAX IS USED
Ventilation	LOCAL EXHAUST IS ADEQUATE
Protective Gloves	NOT REQUIRED
Eye Protection	NORMAL PROTECTION FROM DUST
Other Protective Equipment	NONE IF SOLID. IN HANDLING HOT LIQUID WAX, EYE & HAND PROTECTION SHOULD BE PROVIDED
Disposal Code	O

SECTION IX - Label Data

Protect Eye	NO
Protect Skin	NO
Protect Respiratory	NO
Chronic Indicator	NO
Contact Code	SLIGHT
Fire Code	UNKNOWN
Health Code	UNKNOWN
React Code	UNKNOWN

SECTION X - Transportation Data

Container Quantity	50
Unit of Measure	LB

SECTION XI - Site Specific/Reporting Information

Volatile Organic Compounds (P/G)	0
Volatile Organic Compounds (G/L)	0

SECTION XII - Ingredients/Identity Information

Ingredient #	01
Ingredient Name	NONE LISTED
CAS Number	1005
Percent	0
